

Style Numbers	Luminaire Sketches	Reflector Orientation for Photometric Test	Candela Distribution	File Name	Photometric Type	Location of Maximum Candlepower	Adjustability	Lamp	Lamp Multiplier
---------------	--------------------	--	----------------------	-----------	------------------	---------------------------------	---------------	------	-----------------

T8 Linear Fluorescent - SMALL Reflector

101 102 105 106 109 115			 ITL	35078-2'.IES	C	20°	Adjustable	F17T8	1.00
				35078-3'.IES	C	20°	Adjustable	F25T8	1.00
				35078-4'.IES	C	20°	Adjustable	F32T8	1.00
				35078-5'.IES	C	20°	Adjustable	F40T8	1.00
105 106 109 with visor			 ITL	52765-2'.IES	C	135°	Adjustable	F17T8	1.00
				52765-3'.IES	C	135°	Adjustable	F25T8	1.00
				52765-4'.IES	C	135°	Adjustable	F32T8	1.00
				52765-5'.IES	C	135°	Adjustable	F40T8	1.00
110			 ITL	35078T2'.IES	C	30°	Non-Adjustable	F17T8	1.00
				35078T3'.IES	C	30°	Non-Adjustable	F25T8	1.00
				35078T4'.IES	C	30°	Non-Adjustable	F32T8	1.00
				35078T5'.IES	C	30°	Non-Adjustable	F40T8	1.00
306 301 (dimming applications)			 ITL	49409-2'.IES	C	115°	Adjustable	F17T8	1.00
				49409-3'.IES	C	115°	Adjustable	F25T8	1.00
				49409-4'.IES	C	115°	Adjustable	F32T8	1.00
				49409-5'.IES	C	115°	Adjustable	F40T8	1.00
301 (luminaire tested in cover by others)			 ITL	34926-2'.IES	C	115°	Non-Adjustable	F17T8	1.00
				34926-3'.IES	C	115°	Non-Adjustable	F25T8	1.00
				34926-4'.IES	C	115°	Non-Adjustable	F32T8	1.00
				34926-5'.IES	C	115°	Non-Adjustable	F40T8	1.00



T12 Linear Fluorescent - LARGE Reflector

152			 ITL	37816-3'.IES	C	15°	Adjustable	F36T12HO	1.00
				37816-4'.IES	C	15°	Adjustable	F48T12HO F48T12VHO	1.00 1.53
				37816-5'.IES	C	15°	Adjustable	F60T12HO	1.00