

Ovalinear®

Style M159



elliptipar 
There is no equal™

M159 Versatility



- Compact size integrates easily with site architecture
- Adjustable aiming with locking setscrew
- High color rendition CMH lamps (81-85 CRI) in warm or cool colors (3000K, 4200K)
- Integral, universal-voltage electronic ballast (120-277V)
- Surface, cantilever, pendant and slipfitter mountings

M159 Durability



- Extruded, high-purity aluminum reflector
- Die-cast aluminum ballast compartment with single-piece silicone gasket
- Captive, tamper-resistant stainless steel door fasteners with seize-proof inserts
- Electrostatically-applied thermoset polyester powder coat (1,000-hour salt spray)
- Cold-start electronic ballast (-20° F, -30° C) with superior lamp regulation

M159 Sustainability



- Adjustable asymmetric distribution focuses on target surface, minimizing spill light
- Broad lateral coverage maximizes surface uniformity while minimizing number of fixtures
- CMH offers long lamp life (12,000 hours) and high lumen maintenance (75-80% at 40% life)
- 20, 35 and 70W CMH are efficient (92 lumens per W) and well suited for nighttime surrounds
- Electronic ballast saves 11% in energy over magnetic and allows more fixtures per circuit



THE LIGHTING **QUOTIENT**



[M159 Uplighting Catalog page >>](#)

[M159 Lighting the Vertical Plane Catalog page >>](#)

elliptipar 
There is no equal™

tambient 
Green in any color®